



"Making an Impact at your Event"

IMPACT DEMO CROSS

RULES AND REGULATIONS – DEMO CROSS- 2023

NO CHANGES OR ALTERATIONS OF RULES TO BE MADE EXCEPT BY IMPACT MOTORSPORTS

www.impactmotorsports.ca

NO REFUNDS!!

IMPORTANT: Each driver and mechanic must sign in at registration desk the day of show and have their cars inspected solely to determine compliance with those rules and not for purpose of determining safety of car or participant **NO REFUNDS!**

DRIVER MUST ATTEND DRIVERS' MEETING PRIOR TO DEMOLITION DERBY OR DRIVER WILL BE DISQUALIFIED.

I have read the rules and acknowledge to have received a copy of same and agree that the decision of the Judges is final. I agree to participate at my own risk absolutely. It is a condition of my participation in the contest that I sign a further release of liability in the form to be supplied by Impact Motorsports and I agree to sign such a release.

SPECIAL NOTICE: NO ALCOHOL OR DRUGS ALLOWED IN ANY RESTRICTED (PIT, HOLDING OR PERFORMING) AREA. ANY VIOLATIONS WILL RESULT IN DISQUALIFICATION OF CAR, DRIVER AND CREW. NO REFUNDS!!!

The Impact Motorsports Demolition Derby is promoted as an unusual spectator attraction.

DRIVERS and MECHANICS are subject to and must obey the following rules and regulations which are set up by the promoter and the track where this event is being held:

1. For demo cross each driver must be a minimum age of 16. All 16 & 17 year olds must have a parent or guardians sign an insurance waiver. Guardian must provide photo ID.
2. The original registered driver must drive that vehicle for the entire event. No substituting drivers.
3. Impact Motorsports or promoter reserves the right to approve or reject any and all entries, drivers or pit persons.
4. Only drivers and mechanics who sign the release sheet will be permitted in the pit area or on the track. Driver will receive a free admission to the grounds upon registration of car on day of show. All drivers and pit person must wear supplied pit passes.
5. Impact Motorsports, the promoter, track owner or fair association will not be held responsible for any cars, parts or personal property that may be damaged or stolen, before, during or after the show.
6. It is recommended that each competitor should carry their own liability insurance.
7. Drivers and mechanics should report to the Impact Motorsports sign in area minimum of an hour before the scheduled start time.
8. IMPACT MOTORSPORTS reserves the right to ask all pit persons for photo ID. All drivers and mechanics are in the pit area at their own risk.

Type of Car

1. Any 4-6-8 cylinder hardtop automobile or station wagons. Any style of van, pick-up truck or suburban. Maximum of 1/2 ton. Any year of cars permitted. Demolition derby cars may be used. 4X4 trucks must have all 4X4 parts removed. NO all wheel drives or off road racing cars or trucks. "Stock" like vehicles or demolition derby cars built to the IMPACT rules permitted only.
2. Cars previously run in demos may be considered too battered and unsafe, resulting in disqualification. This is a race not a demo derby.
3. If there is in any question regarding the participant's vehicle it is the driver's responsibility to prove make, model, year, engine etc.

RUNNING

Risk: Demolition derbies are hazardous and high-risk sports; therefore, anyone with a health condition, i.e., concussion, heart problems etc. or who is pregnant should not compete.

Protect yourself. Work Boots, sport equipment – e.g. neck brace, knee pads, shoulder pads, hip pads etc. are recommended.

No bare exposed skin. All drivers **MUST** wear long pants/coveralls or long sleeved shirts. **No exceptions.**

Working seat belt and racing helmet are mandatory. Helmets **MUST** have chin straps. Goggles or face shields are recommended. No motocross style visors.

BRAKES – VEHICLES MUST HAVE DEPENDABLE BRAKES AND MUST BE WORKING PROPERLY BEFORE ENTERING PEN AT ALL TIMES. All boundaries must be observed.

NO DRINKING OF ALCOHOLIC BEVERAGES ON TRACK, EMERGENCY VEHICLE AREA OR IN THE PIT AREA. Any driver or pit person under the influence of alcohol or drugs allowed in the pit area. This will be strictly enforced.

Careless driving in the pit area could result in disqualification.

All cars are to be removed from the fairgrounds or racetrack immediately following the show.

Additional safety regulations may be imposed, depending on track and conditions.

ALL DECISIONS OF THE OFFICIAL ARE FINAL. NO REFUNDS!!

If you think there is a grey area in these rules contact our office and we will put them in black and white for you. NO REFUNDS

PREPARATION OF CAR MUST BE DONE PRIOR TO ARRIVING AT FAIRGROUNDS OR TRACK. DEMO CROSS-OPEN TO CARS-VANS & TRUCKS- MAX ½ TON

1. RIDING ON CAR	Insurance Regulation: No person riding on outside of cars at any time. All drivers and pit person MUST sign in when arriving at the event.
2. FLAMMABLE MATERIAL	Please remove sun visors
3. TRAILER HITCH	Must be removed and all sharp edges must be mashed down prior to derby event. Pickup truck MUST have rear mud flaps min 8" long.
4. GLASS/AIRBAGS	All windows, mirrors, lights, airbags & trim, must be removed prior to derby event. Windshield may be left in place to protect driver.
5. DOORS & NUMBERS	An roof number plate must be securely installed. Every vehicle must have numbers clearly visible on both sides of the car
6. FIRE EXTINGUISHER	Must be within reach of the driver, must work and have a working gauge.
7. BATTERY	One 12 volt car battery may be moved to front passenger floorboard and securely fastened in a box/container clear of all fuel sources. Following inspection it must be covered with a non-flammable shield OR left in stock position under the hood and covered with a rubber mat and secured with an extra strap.
8. GAS TANK	Stock gas tanks may be removed. Must be a steel marine tank, custom steel fuel tank, or certified racing fuel cell. All tanks must be securely fastened down (bolted) in the middle of the back-seat area. Tank must be covered with a non-flammable material after inspection. Maximum 3 gallons gas OR stock tank can be left in stock position if not rusty. Referee has final decision. If left in stock position it is mandatory that an additional strap be added to hold tank in place. No plastic tanks.
9. FUEL LINES	All fuel lines must have leak proof fitting with steel or rubber lines (no clear lines). No exceptions.
10. FUEL SYSTEM	Electric fuel pump must be isolated with a non-flammable material covering lines, tank & pump. Non-flammable covering may be fire resistant blanket or air bag material.
11. HOOD	A 12" opening must be cut in hood over the center of the engine. Hoods must be held down in a minimum of 2 places with seat belts, chain, wire, bolts or weld. No overuse of materials.
12. TRUNK	Trunk, rear hatch or tailgate SHOULD be held down in a minimum of 2 places with seat belts, chain, wire, bolts or weld. No overuse of materials. - OPTIONAL
13. BODY PANELS	Metal may be cut from around wheels for clearance. Front & rear quarter panels may be bolted with up to 5 bolts per panel - maximum 3/8" bolts.
14. DOOR FASTENING	Driver's door may be welded solid. All other doors must be fastened shut with wire, straps, chain, welds or bolts. No overuse of materials. Solid driver's door window screens are not allowed. Mandatory that the driver's door be fastened closed in minimum of 4 places.
15. BRACING	Outside of car may have a 12" X 72" X 1/4" max steel plate applied to driver & passenger doors, bolted in 4 locations (with a maximum 3/4" through bolt) & spot welded 1" every 12". Bevel should not exceed 20°. NO "C" CHANNEL OR ANGLE IRON. Not mandatory.
16. ROLL BAR	Single roll bar up each doorframe, inside or across outside of the roof. Roll bars going across the roof must be through bolted twice through the roof for driver & spectator safety. This roll bar may be welded or bolted to the frame or rockers. An additional bar may be added behind the seat welded or bolted from roll bar to roll bar. Recommend 3" to 4" square tubing or pipe. No excessive use of materials. Not mandatory. Extra bars inside the car may be used for driver's safety. Not Mandatory.
17. WINDSHIELD SPACE	Windshield area may have a safety cage or bars running from the cowl to the roof. Windshields may be left in place. If windshield is removed a bar must be put in place in the driver's windshield area for driver's safety.
18. DASH BAR	Min 3" to Max 4" square tubing mounted doorframe to doorframe, but not to firewall. Not Mandatory. Driver Safety.
19. INTERIOR MODIFICATIONS	No welding of any inside body support seams or firewall seams. All holes in firewall must be covered with a non-flammable material. Large holes in car floors must be repaired with same gauge metal and securely fastened. No reinforcement.
20. BUMPERS	Bumper shocks may be reinforced with flat bar or tubing to help keep bumpers on. Excessive use of material will be asked to be removed. No loading of bumpers. Officials may request a hole be made in bumper for inspection. Bumper layers may be welded together. No metal added. Bumper styles may be swapped. OEM bumpers to be used only. No homemade bumpers. Years or styles of bumpers do not matter. No battering rams permitted. No Reinforcement. Mandatory that both front and rear bumpers are tied up with wire or seat belt in minimum of 2 spots.
21. FRONT GRILL	Stock A.C. condensers permitted in original position. Screens allowed
22. RADIATOR	Must be flushed of anti-freeze and replaced with water only. Overflows must point straight down or positioned so not to harm other drivers & spectators. Floating rad cradles with maximum 1/8" gauge steel angle or flat bar will be allowed - Absolutely no reinforcement to frame or rad cradle. Must be mounted in front of engine.
23. TRANSMISSION COOLER	Is permitted and must be secured in engine compartment. Transmission dipstick must be securely fastened, wired down or have an overflow tube pointing straight down away from drivers or spectators. OR May be re-located to directly behind driver seat, bolted to the back bar and completely covered to the floor with a tin shroud. A minimum of two 1" holes must be made in the floorboard directly below cooler for drainage. Hoses must run straight down under driver seat and be completely covered with non-flammable material. Hose spec: 2500psi single braid hydraulic hose with pressed fittings only, must be rated for 250°F+. Hydraulic hoses must be marked as such by manufacturer. Hydraulic hoses must have pressed fittings only. No other fittings acceptable OR remain stock.
24. DISTRIBUTOR	May be protected. Fresh cars must have 1" away from the firewall. Excessive material will be asked to be removed.
25. SUSPENSION	Suspension must remain stock (movement must occur). Broken or sagging parts may be replaced. It is recommended that rear coil be wired or welded to differential. No spring blocks or added helpers. Rear ends can be exchanged Gears may be welded. Steering columns, drive shafts and rear sway arms may be altered but not reinforced. Ball joints, tie rods, control arms and steering linkage must remain stock. NO REINFORCING ALLOWED. No truck rear ends in cars. No off road suspension permitted. Stock like suspensions.
26. HEADERS	Must be secure, must point upwards and not at other drivers/spectators. Must be a reasonable length or will be asked to be cut or removed. Official's discretion.
27. FRAMES	No welding of frame seams top or bottom. Rusty or bent frames may be repaired with steel no thicker than factory and no longer or wider than 4" on 2 sides only. Over repaired frames will be considered reinforced and will result in alteration or disqualification. Official's discretion. No painting of frames except for the following. Frame repairs must be painted bright orange before arriving for derby event. All repairs to frames must be reported to officials before inspection - over-repaired frames will be asked to be cut - if not - may result in disqualification.
28. DRIVETRAIN PROTECTORS	Protectors may only be fastened to motor or transmission (NO FASTENING TO FRAME OR BODY).
30. MOTOR MOUNTS	Stock mounts may be welded or chained. Home-made mounts are acceptable. Any excessive or added mounts will result in disqualification.
31. TIRES	Maximum 16" D.O.T. Tires must be low aggression. All tires must be filled with air only. Tires may be doubled. No split rims. No screwing tires to rim or studding. All wheel weights must be removed and no welding stem protections. Carry spare 16" D.O.T. mud tires in case track conditions warrant. Referee's discretion. NO OVER AGGRESSIVE TIRES on drive wheels. No triple side walls on drive wheels. Tire tread over 1/4 " deep might be rejected.

